



## Enameled Round Copper Wire

### Product Description

- 1) Self-Solderable Polyurethane Series: QA(UEW), Class 130 °C, Class 155 °C, Class 180 °C;
- 2) Nylon Overcoating Series: QA/N(UEW/N), Class 130 °C, Class 155 °C, Class 180 °C;
- 3) Polyester Series: QZ(PEW), Class 130 °C, Class 155 °C;
- 4) Polyester-imide Series: QZY(EIW), Class 180 °C;
- 5) Solderable Polyester-imide Series: QZYH(SEIW), Class 180 °C;
- 6) Polyester-imide Over coated with Polyamide-imide: Q(ZY/XY) (EI/AIW), Class 220 °C;



Dia. Range: 0.018-3.000mm

## Enameled Round Aluminum Wire

### Product Description

- 1) Polyester/Modified Polyester Round Enameled Aluminum Wire(PEW), Class 130 °C, Class 155 °C;
- 2) Polyester-imide Round Enameled Aluminum Wire(EIW), Class 180 °C, Class 200 °C;
- 3) Polyester-imide/polyamide-imide Round Enameled Aluminum Wire(EI/AIW), Class 200 °C;
- 4) Polyimide Round Enameled Aluminum Wire(PIW), Class 220 °C;



Dia. Range: 0.300-8.000mm

